



- 1、设计压力4.1MPa(600PSI)
Design Pressure 4.1MPa(600PSI)
- 2、设计温度66℃ (150° F)
Design Temperature 66℃ (150° F)
- 3、最低允许温度-10℃ (14° F)
Min Temperature -10℃ (14° F)
- 4、工作介质为PH3-10的水
Media:Water PH3-10
- 5、图纸仅供参考，具体以实物为准
Drawings are for reference only, in kind
- 6、请按照说明书正确使用
Please operate it according to operation manual

长度编号 length	S (mm)	L (mm)	重量 WEIGHT (kg)
1	800 (31.5)	1194 (47)	11.5 (25.3)
2	1816 (71.5)	2210 (87)	14.5 (31.9)
3	2832 (111.5)	3226 (127)	17.5 (38.5)
4	3848 (151.5)	4242 (167)	20.5 (45.1)
4021	412 (16.2)	712 (28)	6.5 (14.3)
4014	235 (9.3)	534 (21)	5.5 (12.1)

12	卡簧Permeate Retaining Ring	2	SUS304
11	挡块Stop dog	6	SUS304
10	挡圈Retaining ring	2	SUS304
09	鞍座Saddle	2-3	TPU(S60D)
07/08	钢带Strap+螺丝screwhead	2-3	A-666, 304+SUS304
06	小O型胶圈Small O-type rubber ring	2	EPDM 512
05	大O型胶圈Large O-type rubber ring	2	EPDM 512
04	密封板Sealboard	2	ABS
03	承压板Pressure plate	2	SB-209, 6061-T651
02	进、出水口钢管Intake and outlet pipe	2	2205
01	壳体Shell	1	环氧+玻纤Epoxy + glass fiber
	名称	数量	材料

SIGNATURE		
DESIGN	NAME	DATE
	陈勇	2018.1.25
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

Winder 河北成达华膜科技有限公司
Hebei Chengda Huamo Technology Co., Ltd

型号 TYPE: 4寸端开600P 单位UNIT: MM

仅供参考，零部件以图纸为准，变更不另行通知