



- 1、设计压力3.1MPa(450PSI)  
Design Pressure 3.1MPa(450PSI)
- 2、设计温度66℃(150° F)  
Design Temperature 66℃(150° F)
- 3、最低允许温度-10℃(14° F)  
Min Temperature -10℃(14° F)
- 4、工作介质为PH3-10的水  
Water working medium PH3-10
- 5、净水口压力为0.88MPa(125PSI)  
Water mouth pressure 0.88 MPa(125 PSI)
- 6、项目5仅在浓水端  
Item 5. At the end of concentrated water only
- 7、图纸仅供参考，具体以实物为准  
Drawings are for reference only, in kind
- 8、请按照说明书正确使用  
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	重量 WEIGHT (kg)
1	700 (27.6)	1460 (57.5)	
2	1716 (67.6)	2476 (97.5)	
3	2732 (107.6)	3492 (137.5)	
4	3748 (147.6)	4508 (177.5)	
5	4764 (187.6)	5524 (217.5)	
6	5780 (227.6)	6540 (257.5)	
7	6796 (267.6)	7556 (297.5)	

17	紧固螺母	2	工程塑料Engineering Plastic
15/16	挡块+挡块FASTENING NUT+BAFFLE FIXING BOLTS	6	SUS304
14	预埋钢圈PREBURIED STEEL RINGS	2	SUS304
12/13	钢带STRAP+螺丝SCREWHEAD (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
11	鞍座SADDLE (3芯以上均为3个)	2-3	TPU (S60D)
10	密封板 SEALBOARD	2	ABS
09	适配器ADAPTOR	2	ABS
08	适配器大/小O型圈ADAPTOR LARGE/SMALL O GLUE	4+4	EPDM 512+硅胶
07	密封板O型圈SEALING PLATE O-RING	2	EPDM 512
06	承载板BEARING PLATE	2	SB-209, 6061-T651
05	止推环THRUST CONE	1	工程塑料Engineering Plastic
04	两圈挡环TWO RINGS	2	SUS304
03	密封胶圈SEALED RUBBER RINGS	4	EPDM 512
02	进、出水口ACCESS TO WATER	2	SUS304
01	壳体SHELL	1	FIBER GLASS +EPOXY
	名称	数量	材料

SIGNATURE		
设计	陈勇	2019.1.31
审核		
审批		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

Winder® 河北成达华膜科技有限公司 Hebei Chengda HuaMo Technology Co., Ltd	
型号 TYPE W80E450	单位UNIT: MM
仅供参考，零部件以图纸为准，变更不另行通知	